


Threaded Whip Receiving Mounts



Steel Thread Mounts

- a : 519.343NP Non-powered
- b : 519.343.RCA RCA Type power connector w/ RCA type pigtail
- c : 519.343 wire in pigtail

Quick Disconnect Receiving Mounts



Stainless Steel QD Mount

Use with quick disconnect whips

- d : SWQDNP: Non-powered
- e : SWQD-PT: wire in pigtail
- f : SWQD-R: RCA Type power connector w/ RCA type pigtail



Heavy Duty Spring Mount

Highly recommended to help reduce whip breakage.

Shown with:
ABM: Angle Bracket Mount
See page 18

Powered:

- g : 519.309 Stainless Steel
- h : 519.30B Zinc Plated Steel



Non-powder

- i : 519.309NP Stainless Steel
- j : 519.30BNP Zinc Plated Steel



Whip Mount Thread to QD Adapters

Thread to Quick Disconnect Adapters:

For use converting 1/2 inch 20 thread whip connection to QD
Available as Adapter Only or in Kit with Receiving QD Mount

Non-powered



- k : SWQD-KIT-NP, (kit)
- l : SWQD-WA-NP (adapter only)

Powered w/ lead



- m : SWQD-KIT-PT (kit)
- n : SWQD-WA (adapter only)

Powered w/detachable RCA lead



- o : SWQD-KIT-R (kit),
- p : SWQD-WA (adapter only)



USA 2115 W. Mountain View Rd., Phoenix, AZ 85021
www.SafetyWhips.com Sales@SafetyWhips.com

TEL 602-424.2500
 FAX 602-424.9777

CANADA 677 - 192 St. #107 Surrey, BC V3S 3X1
www.SafetyWhips.ca Lugo@SafetyWhips.com

TEL 604-560.5080
 FAX 604-560.5090